

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

1. Identification of the product and of the company undertaking

Product details

Trade name:	Primary zinc/air button cell		
Product types	K675ZA	IEC PR 44	ANSI 7003ZD
	K13ZA	IEC PR 48	ANSI 7000ZD
	K312ZA	IEC PR 41	ANSI 7002ZD
	K10ZA	IEC PR 70	ANSI 7005ZD
Voltage:	1.4 V		
Electrochemical system:	Zinc KOH electrolyte oxygen		
Anode (negative electrode):	Zinc		
Cathode (positive electrode):	MnO _x catalyst		

Supplier details

Address:	Strand Europe Ltd Strand House, Galway Road Yateley, Hampshire GU46 6GE
Emergency telephone number:	+44 (0)1252 864533

Legal Remark (U.S.A.)

Safety Data Sheets are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". According to OSHA, Article means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees.

Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard.

Legal remark (EU)

These batteries are not substances or mixtures according to Regulation (EC) No 1907/2006 EC. Instead they have to be regarded as articles; no substances are intended to be released during handling. Therefore there is no obligation to supply a safety data sheet according to Regulation (EC) 1907/2006, Article 31+

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

General remark

This information is provided as a service to our customers. The details presented are in accordance with our present knowledge and experiences. They are no contractual assurances of product attributes.

2. Hazards identification

A sealed zinc/air button cell is not hazardous in normal use (as defined in chapter 7).

In case of mistreatment (prolonged deep discharge, charge, reverse charge, external short circuit) and in case of fault, some electrolyte can leak from the cell through the air holes. In these cases refer to the risk of potassium hydroxide solution (corrosive, pH > 14). Charging may cause rupture. The electrode materials are only hazardous, if the materials are released by mechanical damaging of the cell or if exposed to fire.

3. Composition/information on ingredients

Ingredients

Contents	CAS No.	Classification	R Phrases	Material
0 - 14 %	1313-13-9	Xn;	R 20/22	Manganese oxide
18 - 46 %	7440-66-6	N;	R 50/53	Zinc
1 - 4 %	1310-58-3	Xn; C;	R 22 R 35	Potassium hydroxide
0,01 - 0,06 %	7439-92-1	Repr. Cat. 1; Repr. Cat. 3; Xn; N;	R 61 R 62 R 20/22-33 R50-53	Lead

Full text of Classification and R-phrases: see section 16.

Heavy Metals

Contents	CAS No.	Material
< 5 mg/kg	7440-43-9	Cadmium
< 5 mg/kg	7439-97-6	Mercury (none intentionally introduced, see Chapter 12)

Other Ingredients

Contents	CAS No.	Material
27 - 70 %		Nickel plated
2 - 5 %		Copper
2 - 7 %		Polymers

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

4. First aid measures

Measures at accidental release

After inhalation:	Fresh air. Seek for medical assistance
After skin contact:	Flush affected areas with plenty of water. Remove contaminated cloth immediately. Seek for medical assistance.
After eye contact:	Flush the eye gently with plenty of water (at least 15 minutes). Seek for medical assistance.
After ingestion:	Drink plenty of water. Avoid vomiting. Seek for medical assistance. No trials for neutralization.

5. Fire fighting measures

Suitable extinguishing media:	Use foam, water, or CO ₂ , as appropriate
Extinguishing media with limited suitability:	(none)
Special protection equipment during fire-fighting:	Contamination cloth including breathing apparatus
Special hazard:	(none)

6. Accidental release measures

Person related measures:	Wear personal protective equipment adapted to the situation (protection gloves, cloth)
Environment protection measures:	In the event of battery rupture, prevent skin contact and collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.
Treatment for cleaning:	If battery casing is dismantled, small amounts of electrolyte may leak. Pack the battery including ingredients as described above. Then clean with water (diluted acetic acid may be helpful).

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

7. Handling and storage

Guideline for safe handling:

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into water. Do not throw batteries into fire. Do not short-circuit batteries. Do not recharge primary batteries. Do not open or disassemble batteries.

Storage:

Storage preferably at room temperature (approx. 20°C). Avoid large temperature changes. Avoid direct sunlight. At higher temperature the electrical performance may be reduced. Storage of unpacked batteries can cause short circuit and heat generation.

Storage of large amounts:

If possible, store the batteries in original packaging (short circuit protection); A fire alarm is recommended; For automatic fire extinction consider chapter 5 Fire fighting measures.

Storage category according to TRGS 510:

It is recommended to consider the Technical Rule for Hazardous Substances TRGS 510 - Storage of hazardous substances in non-stationary containers and to handle primary zinc/air button cells according to storage category 11 (combustible solids).

8. Exposure controls/personal protection

Under normal conditions (discharge, avoid prolonged deep discharge) release of ingredients does not occur.

9. Physical and chemical properties

Not applicable if closed.

10. Stability and reactivity

Dangerous reactions: When heated above 60°C the risk of rupture occurs.

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

11. Toxicological information

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 2, 3, and 4.

Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

12. Ecological information

Primary zinc/air button cells do contain lead, and do not contain mercury and cadmium as defined by the European directive 2006/66/EC Article 21.

Mercury has not been intentionally introduced (as distinguished from mercury that may be incidentally present in other materials) in the sense of the U.S.A. Mercury-Containing and Rechargeable Battery Management Act (May 13 1996).

The Regulation on Mercury Content Limitation for Batteries promulgated on 1997-12-31 by the China authorities including the State Administration of Light Industry and the State Environmental Protection Administration defines low mercury as mercury content by weight in battery as less than 0.025% and mercury free as mercury content by weight in battery as less than 0.0001%. And therefore: KODAK primary zinc/air button cells belong to the category of low-mercury battery (mercury content lower than 0.025%).

13. Disposal considerations

USA: Primary zinc/air button cells are classified by the federal government as non-hazardous waste and are safe for disposal in the normal municipal waste stream.

In the European Union, manufacturing, handling and disposal of batteries is regulated on the basis of the DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC. Customers find detailed information on disposal in their specific countries using the web site of the European Portable Batteries Association (http://www.epbaeurope.net/legislation_national.html).

Importers and users outside EU should consider the local law and rules.

In order to avoid short circuit and heating, used zinc/air cells/batteries should never be stored or transported in bulk. Proper measures against short circuit are:

- Storage of batteries in original packaging
- Coverage of the terminals

14. Transport information

General considerations

KODAK primary zinc/air button cells are considered to be dry cell batteries and are unregulated for purposes of transportation by the U.S. Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA), the International Maritime Organization (IMO), the Accord Européen Relatif au Transport International des Marchandises Dangereuses par Route (ADR) and the Règlement concernant le transport international ferroviaire de marchandises Dangereuses (RID).

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

IATA DGR

Special Provision A123: *“Examples of such batteries are: alkali-manganese, zinc-carbon,, nickel-metal hydride and nickel-cadmium batteries. Any electrical battery ... having the potential of a dangerous evolution of heat must be prepared for transport as to prevent (a) a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals...) is forbidden from transport; and (b) accidental activation. The words “Not Restricted” and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued.”*

ADR/RID/IMDG Code

As primary zinc/air button cells are not explicitly mentioned in these Dangerous Goods regulations, there are no special Dangerous Goods shipment requirements for these products.

USA 49 CFR § 172.102 Special Provision 130: *“Dry batteries not specifically covered by another entry in the §172.101 Table are covered by this entry (i.e., Batteries, dry, sealed, n.o.s.) and are not subject to requirements of this subchapter except for the following: [...] (b) Preparation for transport. Batteries and battery-powered device(s) containing batteries must be prepared and packaged for transport in a manner to prevent: (1) A dangerous evolution of heat; (2) Short circuits, including but not limited to the following methods: [...] (ii) Separating or packaging batteries in a manner to prevent contact with other batteries, devices or conductive materials (e.g., metal) in the packagings [...]; and (3) Damage to terminals. If not impact resistant, the outer packaging should not be used as the sole means of protecting the battery terminals from damage or short circuiting. Batteries must be securely cushioned and packed to prevent shifting which could loosen terminal caps or reorient the terminals to produce short circuits.”*

IEC 60086-1

Code of practice for packaging and shipment of primary batteries given in IEC 60086-1:

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

Shock and vibration shall be kept to a minimum. For instance, boxes should not be thrown off trucks, slammed into position or piled so high as to overload battery containers below. Protection from inclement weather should be provided.

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

15. Regulatory information

Marking consideration:

KODAK primary zinc/air button cells conform with the requirements of the Medical Devices Directive 93/42/EEC class 1 and are thus marked with the CE symbol. According to DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC all batteries have to be marked with the crossed bin; according to Article 21 of this directive primary zinc/air button cells have to be marked with the element symbol Pb .

International safety standards:

IEC 60086-5.

Water hazard class:

(according to German Federal Water Management Act) non-water pollution according to VwVwS Appendix 1 (No. 1443 and 766)

16. Other information

Full text of Classification and R Phrases referred to under sections 2 and 3

Classification

Repr. Cat. 1 toxic for reproduction category 1
Repr. Cat. 3 toxic for reproduction category 3
C Corrosive
Xn Harmful
N Dangerous for the environment

R Phrases

20/22 Harmful by inhalation and if swallowed.
22 Harmful if swallowed.
33 Danger of cumulative effects.
35 Causes severe burns.
61 May cause harm to the unborn child.
62 Possible risk of impaired fertility.
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

PRIMARY ZINC/AIR BUTTON CELL, MERCURY FREE

Note: Date of issue of the transport regulations: ADR 2013, RID 2013, IATA 2013, IMDG 2010, DOT / 49 CFR 2013.
Latest covered modification of the European Battery Directive 2006/66/EC: Directive 2008/103/EC.

Issued by: Strand Europe Ltd.

Contact person: Kodak Batteries - Technology Department
Tel. +44 (0) 1252 864520
E-Mail: kodakbatteries@strandeurope.com